

EARTHMAX SR 45 H2 - Technische Daten



Description

EARTHMAX SR 45 H2 ist ein speziell für starre Muldenkipper entwickelter All Steel Radialreifen. Das einzigartige Laufflächenmuster mit E-4 Tiefe bietet geringen Verschleiß und reduziert Vibrationen und Geräusche auf ein Minimum. EARTHMAX SR 45 H2 eignet sich vortrefflich für alle Arbeiten, die Traktion und Stabilität erfordern. Dank seiner All-Steel-Struktur gewährleistet der Reifen hervorragende Stich- und Schnittfestigkeit sowie ein verlängertes Reifenleben. Erhältlich mit Standardgummimischung, hitzebeständig oder schnittfest.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Starrer Muldenkipper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

Dimensions US Standard

Usa code	94060221
TMPH	228
Overall Width (inch)	26
Overall Diameter (inch)	85.8
Static Loaded Radius (inch)	38.5
Rolling Circumference (inch)	259.7
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 05.12.2023 02:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..