

EARTHMAX SR 45 H2 - Datenblatt



Description

EARTHMAX SR 45 H2 ist ein speziell für starre Muldenkipper entwickelter All Steel Radialreifen. Das einzigartige Laufflächenmuster mit E-4 Tiefe bietet geringen Verschleiß und reduziert Vibrationen und Geräusche auf ein Minimum. EARTHMAX SR 45 H2 eignet sich vortrefflich für alle Arbeiten, die Traktion und Stabilität erfordern. Dank seiner All-Steel-Struktur gewährleistet der Reifen hervorragende Stich- und Schnittfestigkeit sowie ein verlängertes Reifenleben. Erhältlich mit Standardgummimischung, hitzebeständig oder schnittfest.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Starrer Muldenkipper

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	333
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		660	2180	978	6597	TL	435
24.00 R 35	HEAT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	435
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	390
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	390

Printed on 02.12.2023 03:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..