

EARTHMAX SR 452 - Technische Daten



Description

EARTHMAX SR 452 ist ein All-Steel-Radialreifen, der speziell für artikulierte Muldenkipper bei Transportarbeiten entwickelt wurde. Das einzigartige, tiefe Reifenprofil Klasse E-4 verleiht erstklassige Traktion und hervorragende Hitzebeständigkeit. Es reduziert Vibrationen und Geräusche auf ein Minimum und bietet ausgezeichnetes Handling und besten Komfort. Die robuste Stahlkarkasse mit Stahlgürteln verleiht außerordentliche Stabilität sowie Schnitt- und Stichfestigkeit. Der quadratisch geformte Schulterbereich von EARTHMAX SR 452 steht für besten Bodenkontakt und exzellente Manövrierbarkeit.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Starrer Muldenkipper

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 24.00 R 35 |
| LI/SS | 209 B |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94063383 |
| TMPH | 243 |
| Overall Width (inch) | 26 |
| Overall Diameter (inch) | 85.4 |
| Static Loaded Radius (inch) | 39.2 |
| Rolling Circumference (inch) | 264.9 |
| Rim Rec | 17.00/3.5 |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (lbs)

| mph / psi | 73 | 76 | 80 | 83 | 87 | 91 | 94 | 98 | 102 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 30900 | 32000 | 34200 | 35300 | 36400 | 37500 | 38600 | 39700 | 40800 |

Printed on 05.12.2023 20:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..