

## EARTHMAX SR 45 - Technische Daten



### Description

EARTHMAX SR 45 ist ein speziell für starre Muldenkipper entwickelter All Steel Radialreifen. EARTHMAX SR 45 ist der ideale Reifen für alle Arbeiten, die hohe Traktion erfordern.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Starrer Muldenkipper

|           |                   |
|-----------|-------------------|
| Version   | STANDARD COMPOUND |
| Type      | TL                |
| Tyre Size | 18.00 R 33        |
| LI/SS     | 195 B             |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94064830  |
| TMPH                         | 151       |
| Overall Width (inch)         | 19.9      |
| Overall Diameter (inch)      | 73.6      |
| Static Loaded Radius (inch)  | 33.7      |
| Rolling Circumference (inch) | 220.8     |
| Rim Rec                      | 13.00/2.5 |
| Star Rating                  | ***       |
| TRA Code                     | E4        |

## Load capacity (lbs)

| mph / psi | 105   | 109   | 112   | 116   |
|-----------|-------|-------|-------|-------|
| 30        | 24700 | 25400 | 26000 | 26800 |

Printed on 20.04.2024 15:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..