



EARTHMAX SR 47 TP - Datenblatt

Description

Der EARTHMAX SR 47 TP (E-4) ist ein Vollstahl-Radialreifen, der speziell für starre Transportfahrzeuge konzipiert wurde, die unter Bedingungen arbeiten, welche maximale Traktion und Widerstandsfähigkeit gegen Durchschläge erfordern. Die Tiefe E-4 des Profils sorgt auch bei langen Strecken für eine langsame Abnutzung. Auf diese Weise werden Ausfallzeiten verringert und die Produktivität gesteigert. Der EARTHMAX SR 47 TP eignet sich perfekt für sämtliche Aufgaben, bei denen es insbesondere auf schlammigem oder rutschigem Gelände sowohl auf Traktion als auch auf Stabilität ankommt. Erhältlich in Standard- und schnittfesten Mischungen.

UM

US Standard

Construction



RADIAL

Machinery

OTR: Starrer Muldenkipper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94074204	E4	**	209 B	17.00/3.5	--	25.6	86	38.8	260.8	TL	258
24.00 R 35	STANDARD COMPOUND	94074211	E4	**	209 B	17.00/3.5	--	25.6	86	38.8	260.8	TL	301

Printed on 01.05.2024 11:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..