

## EARTHMAX SR 475 - Technische Daten



### Description

EARTHMAX SR 475 ist ein radialer All-Steel-Reifen, der speziell für starre Muldenkipper entworfen wurde. Er ist ideal zum Einsatz in harter und felsiger Umgebung. Das einzigartige Laufflächenmuster erzeugt weniger Hitze bei warmem Klima und verleiht erstklassige Traktion. Die robuste All-Steel-Karkasse mit Stahlbändern bietet ausgezeichnete Stabilität und Resistenz gegen Schnitte und Risse. EARTHMAX SR 475 wurde mit einer quadratischen Schulter entwickelt, die erstklassiges Handling bei optimalem Bodenkontakt bietet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Starrer Muldenkipper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions US Standard

Usa code	94066933
TMPH	243
Overall Width (inch)	25.7
Overall Diameter (inch)	85
Static Loaded Radius (inch)	38.2
Rolling Circumference (inch)	259.4
Rim Rec	17.00/3.5
Star Rating	**
TRA Code	E4

## Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	30900	32000	34200	35300	36400	37500	38600	39700	40800

Printed on 26.04.2024 11:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..