

EARTHMAX SR 47 - Technische Daten



Description

EARTHMAX SR 47 E4 wurde speziell für starre Muldenkipper entwickelt, die für harte Herausforderungen im Transportbereich wie beispielsweise in Steinbrüchen eingesetzt werden. Die **All-Steel**-Karkasse bietet gemeinsam mit den extra robusten Stahlgürteln außergewöhnliche Stabilität und hervorragende Reiß- und Durchstichfestigkeit.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Starrer Muldenkipper

Version	HEAT RESISTANT
Type	TL
Tyre Size	18.00 R 33
LI/SS	191 B

Dimensions International Standard

TKPH	228
Overall Width (mm)	510
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	867
Rolling Circumference (mm)	5674
Rim Rec	13.00/2.5
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	8500	8750	9000	9250	9750	10000	10300	10600	10900

Printed on 23.04.2024 18:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..