

## EARTHMAX SR 47 - Technische Daten



### Description

EARTHMAX SR 47 E4 wurde speziell für starre Muldenkipper entwickelt, die für harte Herausforderungen im Transportbereich wie beispielsweise in Steinbrüchen eingesetzt werden. Die **All-Steel**-Karkasse bietet gemeinsam mit den extra robusten Stahlgürteln außergewöhnliche Stabilität und hervorragende Reiß- und Durchstichfestigkeit.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Starrer Muldenkipper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	21.00 R 35
LI/SS	201 B

## Dimensions International Standard

TKPH	261
Overall Width (mm)	585
Overall Diameter (mm)	2045
Static Loaded Radius (mm)	944
Rolling Circumference (mm)	6313
Rim Rec	15.00/3.0
Rim Alt	17.00/3.0
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	11200	11500	11800	12150	12850	13200	13600	14000	14500

Printed on 23.04.2024 17:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..