

## EARTHMAX SR 49 - Technische Daten



### Description

EARTHMAX SR 49 (L-4) ist ein All-Steel Radialreifen, der speziell für Radlader und Planierer, für Fahrlader (LHD) und flache Dumper entwickelt wurde. EARTHMAX SR 49 bietet hervorragende Leistung im harten Bergbaueinsatz, bei dem ausgezeichnete Traktion und Stabilität gefordert ist. Der Reifen hat ein richtungsgebundenes Muster und ist aus einer speziellen, schnittfesten Gummimischung, die erstklassige Beständigkeit bietet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Fahrlader LHD • Radlader • flache Dumper

|           |                        |
|-----------|------------------------|
| Version   | CUT RESISTANT COMPOUND |
| Type      | TL                     |
| Tyre Size | 35/65 R 33             |
| LI/SS     | 224 A2                 |

## Dimensions US Standard

|                              |           |
|------------------------------|-----------|
| Usa code                     | 94045082  |
| Overall Width (inch)         | 35.4      |
| Overall Diameter (inch)      | 81.1      |
| Static Loaded Radius (inch)  | 35        |
| Rolling Circumference (inch) | 241.1     |
| Rim Rec                      | 28.00/3.5 |
| Rim Alt                      | --        |
| Star Rating                  | **        |
| TRA Code                     | L4        |

## Load capacity (lbs)

| mph / psi | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 52000 | 55100 | 56800 | 58400 | 60000 | 61500 |

Printed on 06.05.2024 16:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..