

EARTHMAX SR 49 - Technische Daten



Description

EARTHMAX SR 49 (L-4) ist ein All-Steel Radialreifen, der speziell für Radlader und Planierer, für Fahrlader (LHD) und flache Dumper entwickelt wurde. EARTHMAX SR 49 bietet hervorragende Leistung im harten Bergbaueinsatz, bei dem ausgezeichnete Traktion und Stabilität gefordert ist. Der Reifen hat ein richtungsgebundenes Muster und ist aus einer speziellen, schnittfesten Gummimischung, die erstklassige Beständigkeit bietet.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Planierer • Fahrlader LHD • Radlader • flache Dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	45/65 R 45
LI/SS	245 A2

Dimensions US Standard

Usa code	94067572
Overall Width (inch)	44.5
Overall Diameter (inch)	107.5
Static Loaded Radius (inch)	46.9
Rolling Circumference (inch)	319.4
Rim Rec	36.00/4.5
Star Rating	**
TRA Code	L4

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	96500	99000	102000	104500	110000	113500

Printed on 06.05.2024 22:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..