

EARTHMAX SR 49 - Datenblatt



Description

EARTHMAX SR 49 (L-4) ist ein All-Steel Radialreifen, der speziell für Radlader und Planierer, für Fahrlader (LHD) und flache Dumper entwickelt wurde. EARTHMAX SR 49 bietet hervorragende Leistung im harten Bergbaueinsatz, bei dem ausgezeichnete Traktion und Stabilität gefordert ist. Der Reifen hat ein richtungsgebundenes Muster und ist aus einer speziellen, schnittfesten Gummimischung, die erstklassige Beständigkeit bietet.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Planierer • Fahrlader LHD • Radlader • flache Dumper

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
35/65 R 33	CUT RESISTANT COMPOUND	94057115	L4	***	229 A2	28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94057108	E4/L4	****/***		28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94045082	L4	**	224 A2	28.00/3.5	--	35.4	81.1	35	241.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94051939	E4	****		28.00/3.5	--	35.4	81.1	35	241.1	TL
45/65 R 45	CUT RESISTANT COMPOUND	94067572	L4	**	245 A2	36.00/4.5		44.5	107.5	46.9	319.4	TL

Printed on 06.05.2024 16:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..