

EARTHMAX SR 50 - Technische Daten



Description

EARTHMAX SR 50 (L-5) ist ein speziell für Lader entwickelter All Steel Radialreifen. Die resistente Karkasse und der Flankenschutz machen den Reifen ideal zum Einsatz unter anspruchsvollen Arbeitsbedingungen. EARTHMAX SR 50 wurde mit einer speziellen, schnittfesten Gummimischung hergestellt, die hervorragende Verschleißfestigkeit bietet. Die Bediener werden die erstklassige Traktion, Stabilität und den Fahrkomfort zu schätzen wissen.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

Dimensions International Standard

Overall Width (mm)	690
Overall Diameter (mm)	1772
Static Loaded Radius (mm)	806
Rolling Circumference (mm)	5334
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	12850	13200	14000	14500	15000

Printed on 24.04.2024 19:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..