

## EARTHMAX SR 50 - Technische Daten



### Description

EARTHMAX SR 50 (L-5) ist ein speziell für Lader entwickelter All Steel Radialreifen. Die resistente Karkasse und der Flankenschutz machen den Reifen ideal zum Einsatz unter anspruchsvollen Arbeitsbedingungen. EARTHMAX SR 50 wurde mit einer speziellen, schnittfesten Gummimischung hergestellt, die hervorragende Verschleißfestigkeit bietet. Die Bediener werden die erstklassige Traktion, Stabilität und den Fahrkomfort zu schätzen wissen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	202 A2

## Dimensions US Standard

Usa code	94032303
Overall Width (inch)	27.2
Overall Diameter (inch)	69.8
Static Loaded Radius (inch)	31.7
Rolling Circumference (inch)	210
Rim Rec	22.00/3.0
Star Rating	*
TRA Code	L5

## Load capacity (lbs)

mph / psi	58	62	65	69	73
5	28300	29100	30900	32000	33100

Printed on 22.02.2024 17:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..