

EARTHMAX SR 51 - Technische Daten



Description

EARTHMAX SR 51 (L-5) ist ein **All Steel** Reifen, der speziell für Lader und Planiererraupen entwickelt wurde. EARTHMAX SR 51 eignet sich für mittlere bis schwere Einsatzbedingungen, die eine höhere Durchstoßfestigkeit und Flankenschutz bei ausgezeichneter Traktionsleistung erfordern.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Planierer • Radlader

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 20.5 R 25 |
| LI/SS | 186 A2 |

Dimensions International Standard

| | |
|----------------------------|-----------|
| Overall Width (mm) | 539 |
| Overall Diameter (mm) | 1545 |
| Static Loaded Radius (mm) | 703 |
| Rolling Circumference (mm) | 4650 |
| Rim Rec | 17.00/2.0 |
| Star Rating | * |
| TRA Code | L5 |

Load capacity (Kg)

| km/h / bar | 4.00 | 4.25 | 4.50 | 4.75 | 5.00 |
|------------|------|------|------|------|------|
| 10 | 8000 | 8250 | 8750 | 9000 | 9500 |

Printed on 24.04.2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..