

## EARTHMAX SR 51 - Technische Daten



### Description

EARTHMAX SR 51 (L-5) ist ein **All Steel** Reifen, der speziell für Lader und Planiermaschinen entwickelt wurde. EARTHMAX SR 51 eignet sich für mittlere bis schwere Einsatzbedingungen, die eine höhere Durchstoßfestigkeit und Flankenschutz bei ausgezeichneter Traktionsleistung erfordern.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	195 A2

## Dimensions International Standard

Overall Width (mm)	612
Overall Diameter (mm)	1660
Static Loaded Radius (mm)	743
Rolling Circumference (mm)	4882
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L5

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	10300	10600	11200	11500	12150

Printed on 24.04.2024 11:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..