

## EARTHMAX SR 55 - Technische Daten



### Description

EARTHMAX SR 55 (L-5) S ist ein All Steel Radialreifen, der speziell für Lader, Planierer und flache Dumper entwickelt wurde, die unter härtesten Bedingungen in Steinbrüchen, im Bergbau und auf Schrottplätzen zum Einsatz kommen. Dank der hervorragenden Schnittfestigkeit durch das extra tiefe und solide Laufflächenmuster ist EARTHMAX SR 55 in der Lage, maximale Produktivität bei äußerst geringen Stillstandzeiten zu erreichen. Die Bediener der Fahrzeuge werden die außergewöhnliche Stabilität zu schätzen wissen.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Fahrlader LHD • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	17.5 R 25
LI/SS	188 A2

## Dimensions International Standard

Overall Width (mm)	453
Overall Diameter (mm)	1399
Static Loaded Radius (mm)	630
Rolling Circumference (mm)	4211
Rim Rec	14.00/1.5
Star Rating	***
TRA Code	L5S

## Load capacity (Kg)

km/h / bar	6.75	7.00	7.25	7.50	7.75	8.00
10	8750	9000	9250	9500	9750	10000

Printed on 25.04.2024 20:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..