

## EARTHMAX SR 57 - Technische Daten



### Description

EARTHMAX SR 57 ist ein All-Steel-Radialreifen, der speziell für Lader, Planierer und Universalfahrzeuge im Untertagebau entworfen wurde. Der Reifen verleiht erstklassige Traktion, Stabilität und Komfort auf schwierigem, felsigen Gelände. Das extra tiefe L-5 Laufflächenprofil und die speziell formulierte Gummimischung UMS (underground mine service) verleihen eine größere Verschleißfestigkeit neben außerordentlicher Widerstandsfähigkeit gegenüber Schnitten an Felsen und Stichen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Fahrlader LHD • Radlader

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	10.00 R 15

## Dimensions US Standard

Usa code	94065615
Overall Width (inch)	10.9
Overall Diameter (inch)	36.1
Rim Rec	7.50
Rim Alt	7.00
Star Rating	*
TRA Code	L5

## Load capacity (lbs)

mph / psi	102
3.7	7720

Printed on 26.04.2024 23:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..