

## EARTHMAX SR 57 - Datenblatt



### Description

EARTHMAX SR 57 ist ein All-Steel-Radialreifen, der speziell für Lader, Planierer und Universalfahrzeuge im Untertagebau entworfen wurde. Der Reifen verleiht erstklassige Traktion, Stabilität und Komfort auf schwierigem, felsigen Gelände. Das extra tiefe L-5 Laufflächenprofil und die speziell formulierte Gummimischung UMS (underground mine service) verleihen eine größere Verschleißfestigkeit neben außerordentlicher Widerstandsfähigkeit gegenüber Schnitten an Felsen und Stichen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Planierer • Fahrlader LHD • Radlader

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	Type
10.00 R 15	CUT RESISTANT COMPOUND	94065615	L5	*		7.50	7.00	10.9	36.1	TT
7.50 R 15	CUT RESISTANT COMPOUND	94051687	L5	*		6.00	6.5	8.8	33.3	TT
8.25 R 15	CUT RESISTANT COMPOUND	94052783	L5	*		6.50	7.00	9.4	34.6	TT
10.00 R 20	CUT RESISTANT COMPOUND	94073290	L5	*		7.5		10.7	43.5	TT
12.00 R 20	CUT RESISTANT COMPOUND	94057160	L5	*		8.50		12.5	46.5	TT
18.00 R 25	CUT RESISTANT COMPOUND	94063307	L5	**	204 A2	13.00/2.5		20.3	65	TL

Printed on 26.04.2024 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..