

EM 936 SUPER - Technische Daten



Description

EM 936 SUPER wurde speziell für Bagger und Teleskoplader bei Bagger- und Ladearbeiten sowie Transportanwendungen entworfen. Dank der um 8-10% vergrößerten Laufflächenbreite gewährleistet EM 936 SUPER ausgezeichnete Stabilität und verbesserten Fahrkomfort. Dabei bietet er einen hohen Level an Manövrierbarkeit sowie ausgezeichnete Traktion auch unter schweren Betriebsbedingungen.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Bagger

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	145 B

Dimensions US Standard

Usa code	94061860
Ply Rating	14
Section Width (inch)	10.9
Overall Diameter (inch)	42.5
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	131.3
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

Load capacity (lbs)

mph / psi	94
30	6395

Printed on 02.12.2023 14:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..