

## EM 936 SUPER - Technische Daten



### Description

EM 936 SUPER wurde speziell für Bagger und Teleskoplader bei Bagger- und Ladearbeiten sowie Transportanwendungen entworfen. Dank der um 8-10% vergrößerten Laufflächenbreite gewährleistet EM 936 SUPER ausgezeichnete Stabilität und verbesserten Fahrkomfort. Dabei bietet er einen hohen Level an Manövrierbarkeit sowie ausgezeichnete Traktion auch unter schweren Betriebsbedingungen.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Bagger

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20
LI/SS	146 B

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	277
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3336
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
TRA Code	E2

## Load capacity (Kg)

km/h / bar	7.50
50	3000

Printed on 05.12.2023 23:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..