

EM 936 - Technische Daten



Description

EM 936 wurde speziell für Bagger und Teleskoplader bei Bagger- und Ladearbeiten entworfen. Eine Große eignet sich dagegen auch für Planierer und Lader bei Planier-, Lade- und Transportarbeiten. EM 936 zeichnet sich durch erstklassigen Fahrkomfort und verbesserte Selbstreinigungseigenschaften aus. Ebenfalls bietet er einen hohen Level an Manövrierbarkeit sowie ausgezeichnete Traktion auch unter schweren Betriebsbedingungen. Die Ausführung "special" ist aus einer speziellen Gummimischung hergestellt.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Bagger • Teleskoplader

| | |
|-----------|--------------------------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 16.0/70 - 20 (400 / 70 -20) |
| LI/SS | 149 B/166 A2 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94049325 |
| Ply Rating | 14 |
| Overall Width (inch) | 15.9 |
| Overall Diameter (inch) | 42.9 |
| Static Loaded Radius (inch) | 18.9 |
| Rolling Circumference (inch) | 129.7 |
| Rim Rec | 13 SDC |
| Rim Alt | 13 |
| TRA Code | E2 |

Load capacity (lbs)

| mph / psi | 51 | 65 |
|-----------|------|-------|
| 30 | 7160 | - |
| 5 | - | 11680 |

Printed on 11.12.2023 13:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..