

## EM 937 E3 (L) - Technische Daten



### Description

EM 937 (E-3/L-3) wurde speziell zum Einsatz von Ladern und Baggerladern in Bagger- bzw. Ladeanwendungen entworfen, je nach Größe. Der Reifen wartet mit ausgezeichneter Beständigkeit und hervorragende Schnitt- und Reißfestigkeit auf.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrie: Baggerlader • Radlader

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

## Dimensions US Standard

Usa code	94015405
Ply Rating	20
Overall Width (inch)	14.8
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	161.6
Rim Rec	10.00/1.5
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	69	102
30	10200	-
5	-	18700

Printed on 26.04.2024 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..