

F 240 - Technische Daten



Description

F 240 ist ein Reifen für Anwendungen in der Forstwirtschaft zur Bewegung von Baumstämmen. Das Laufflächenprofil verleiht hervorragende Traktionseigenschaften neben ausgezeichneter Selbstreinigung und guten Steuermöglichkeiten. Die erstklassige Gummimischung der Lauffläche gewährleistet außergewöhnliche Widerstandsfähigkeit gegenüber Schnitten und Abnutzung. Dies zeigt sich in einem längeren Betriebsleben. F 240 weist eine breite Aufstandsfläche für bessere Stabilität auf.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Holzschlepper

Version	STANDARD
Type	TT
Tyre Size	400 - 15.5 (400 - 15.5)

Dimensions US Standard

Usa code	94051588
Ply Rating	12
Section Width (inch)	15.9
Overall Diameter (inch)	34.1
Rim Rec	AG 13.00
ECE	E11-106R-004260
TRA Code	LS2

Load capacity (lbs)

mph / psi	55
20	6945

Printed on 27.04.2024 00:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..