

FARM 2000 PLUS - Technische Daten



Description

FARM 2000 PLUS ist ein Landwirtschaftsreifen, der sich durch eine größer Anzahl von Stollen für bessere Leistungen im Einsatz auf dem Feld auszeichnet. Das tiefe Laufflächenprofil gewährleistet ein verlängertes Reifenleben und ausgezeichnete Traktion, während die erstklassige Gummimischung bessere Durchstichfestigkeit bietet. Neben hervorragenden Selbstreinigungseigenschaften weist FARM 2000 PLUS speziell entworfene Stollenwinkel auf, sodass sich der Reifen besonders für Feld- und Transportanwendungen eignet.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	139 A8

Dimensions US Standard

Usa code	94043750
Ply Rating	12
Section Width (inch)	17.3
Overall Diameter (inch)	56.5
Static Loaded Radius (inch)	25.9
Rolling Circumference (inch)	169.7
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	5360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23.04.2025 17:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..