

FARM 2000 - Technische Daten



Description

FARM 2000 ist ein Reifen für Traktoren bei der Bodenbearbeitung. Er wurde mit einer speziellen, schnitt- und reißfesten Gummimischung entwickelt, die ausgezeichnete Beständigkeit bietet. Dank der robusten Karkasse zeichnet sich FARM 2000 mit hoher Tragfähigkeit aus. Er verleiht auch hervorragende Traktion und beste Selbstreinigungseigenschaften.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	8.3 - 24
LI/SS	101 A8

Dimensions US Standard

Usa code	94051908
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	39.2
Static Loaded Radius (inch)	18.6
Rolling Circumference (inch)	119.4
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-004094
TRA Code	R1

Load capacity (lbs)

	mph / psi	45
	20	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16.02.2025 07:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..