FARM HIGHWAY TOUGH - Technische Daten

Description

FARM HIGHWAY TOUGH ist ein Hochgeschwindigkeitsreifen, der speziell für Transportanwendungen und zur Bodenbearbeitung mit Anhängern und landwirtschaftlichen Geräten entworfen wurde. Er bietet hohe Tragfähigkeit auch bei hohen Geschwindigkeiten sowie ein langes Reifenleben.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	10.00 - 15 FI
LI/SS	128 J

Dimensions International Standard

Ply Rating	8
Section Width (mm)	274
Overall Diameter (mm)	853
Rim Rec	8 LB
ECE	E11-54R-0017870

Load capacity (Kg)

km/h / bar	4.10
100	1800

Printed on 27.04.2024 04:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..