

FARM SPECIAL - Datenblatt



Description

FARM SPECIAL ist ein Traktorenreifen, der sich auszeichnet für Arbeiten auf dem Feld eignet. Die robuste Karkasse steht für hohe Durchstoßfestigkeit sowie ein längeres Betriebsleben, während die abgerundete Schulter Bodenschäden vermeidet und so die wertvollen Kulturpflanzen schützt. FARM SPECIAL zeichnet sich durch ein besonderes Laufflächendesign mit sogenannten Mud Breakers aus, die den Schlamm brechen und die Selbstreinigung unterstützen. Außerdem verleihen die doppelwinkligen Stollen hervorragende Traktionseigenschaften bei geringem Schlupf.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | TKPH | ECE |
|---------------------------|----------|----------|--------|----|---------|-------------|-----|------|-----|------|-----|------|------|-----------------|
| 11.2 - 24 | STANDARD | R1 | 116 A6 | 8 | W 10 | W 9 | 285 | 1095 | 509 | 3283 | | TT | | E11-106R-005528 |
| 12.4 - 24 | STANDARD | R1 | 121 A6 | 8 | W 11 | W 9 ; W 10 | 320 | 1155 | 534 | 3504 | 550 | TT | | E11-106R-005529 |
| 13.6 - 24 | STANDARD | R1 | 123 A6 | 8 | W 12 | W 11 | 350 | 1205 | 554 | 3635 | | TT | | E11-106R-005530 |
| 14.9 - 24 | STANDARD | R1 | 128 A6 | 8 | W 13 | W 11 ; W 12 | 378 | 1255 | 572 | 3775 | 600 | TT | | E11-106R-005531 |
| 9.5 - 24 | STANDARD | R1 | 112 A6 | 8 | W 8 | W 7 | 240 | 1050 | 491 | 3194 | | TT | | E11-106R-005527 |
| 11.2 - 28 | STANDARD | R1 | 118 A6 | 8 | W 10 | W 9 | 285 | 1205 | 563 | 3694 | 575 | TT | | E11-106R-005532 |
| 12.4 - 28 | STANDARD | R1 | 123 A6 | 8 | W 11 | W 9 ; W 10 | 315 | 1265 | 589 | 3853 | 600 | TT | | E11-106R-005533 |
| 13.6 - 28 | STANDARD | R1 | 125 A6 | 8 | W 12 | W 11 | 350 | 1310 | 610 | 3985 | 625 | TT | | E11-106R-005534 |
| 14.9 - 28 | STANDARD | R1 | 130 A6 | 8 | W 13 | W 11 ; W 12 | 375 | 1355 | 620 | 4105 | 650 | TT | | E11-106R-005535 |
| 16.9 - 30 | STANDARD | R1 | 137 A6 | 8 | W 15 L | W 14 L | 431 | 1469 | 671 | 4456 | | TT | | E11-106R-005536 |
| 18.4 - 30 | STANDARD | R1 | 139 A6 | 8 | W 16 L | W 15 L | 451 | 1533 | 689 | 4599 | | TT | | E11-106R-005537 |
| 12.4 - 32 | STANDARD | R1 | 124 A6 | 8 | W 11 | W 9 ; W 10 | 320 | 1360 | 634 | 4137 | | TT | | E11-106R-005538 |
| 13.6 - 36 | STANDARD | R1 | 129 A6 | 8 | W 12 | W 11 | 345 | 1515 | 704 | 4591 | | TT | | E11-106R-005539 |
| 13.6 - 38 (14.00 - 38) | STANDARD | R1 | 131 A6 | 8 | W 12 | W 11 | 345 | 1565 | 736 | 4874 | 750 | TT | 1 | E11-106R-005540 |
| 14.00 - 38 (13.6 - 38) | STANDARD | R1 | 131 A6 | 8 | W 12 | W 11 | 345 | 1565 | 736 | 4874 | 750 | TT | | E11-106R-004381 |
| 15.5 - 38 | STANDARD | R1 | 133 A6 | 8 | W 14 L | | 394 | 1575 | 731 | 4813 | | TT | | E11-106R-005541 |

Printed on 27.04.2024 09:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..