

## FARM SPECIAL - Datenblatt



### Description

FARM SPECIAL ist ein Traktorenreifen, der sich auszeichnet für Arbeiten auf dem Feld eignet. Die robuste Karkasse steht für hohe Durchstoßfestigkeit sowie ein längeres Betriebsleben, während die abgerundete Schulter Bodenschäden vermeidet und so die wertvollen Kulturpflanzen schützt. FARM SPECIAL zeichnet sich durch ein besonderes Laufflächendesign mit sogenannten Mud Breakers aus, die den Schlamm brechen und die Selbstreinigung unterstützen. Außerdem verleihen die doppelwinkligen Stollen hervorragende Traktionseigenschaften bei geringem Schlupf.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Traktor

| SIZE                      | Version  | USACode  | TRA Code | LI/SS  | PR | RIM REC | RIM ALT     | SW   | OD   | SLR  | RC    | Type | TMPH | ECE             |
|---------------------------|----------|----------|----------|--------|----|---------|-------------|------|------|------|-------|------|------|-----------------|
| 11.2 - 24                 | STANDARD | 94060795 | R1       | 112 A8 | 8  | W 10    | W 9         | 11.2 | 43.1 | 20   | 129.3 | TT   | 0    | E11-106R-005528 |
| 12.4 - 24                 | STANDARD | 94060696 | R1       | 118 A8 | 8  | W 11    | W 9 ; W 10  | 12.6 | 45.5 | 21   | 138   | TT   | 0    | E11-106R-005529 |
| 13.6 - 24                 | STANDARD | 94060702 | R1       | 120 A8 | 8  | W 12    | W 11        | 13.8 | 47.4 | 21.8 | 143.1 | TT   | 0    | E11-106R-005530 |
| 14.9 - 24                 | STANDARD | 94060719 | R1       | 124 A8 | 8  | W 13    | W 11 ; W 12 | 14.9 | 49.4 | 22.5 | 148.6 | TT   | 0    | E11-106R-005531 |
| 9.5 - 24                  | STANDARD | 94060689 | R1       | 108 A8 | 8  | W 8     | W 7         | 9.4  | 41.3 | 19.3 | 125.7 | TT   | 0    | E11-106R-005527 |
| 11.2 - 28                 | STANDARD | 94060337 | R1       | 114 A8 | 8  | W 10    | W 9         | 11.2 | 47.4 | 22.2 | 145.4 | TT   | 0    | E11-106R-005532 |
| 12.4 - 28                 | STANDARD | 94060726 | R1       | 120 A8 | 8  | W 11    | W 9 ; W 10  | 12.4 | 49.8 | 23.2 | 151.7 | TT   | 0    | E11-106R-005533 |
| 13.6 - 28                 | STANDARD | 94060801 | R1       | 122 A8 | 8  | W 12    | W 11        | 13.8 | 51.6 | 24   | 156.9 | TT   | 0    | E11-106R-005534 |
| 14.9 - 28                 | STANDARD | 94060818 | R1       | 126 A8 | 8  | W 13    | W 11 ; W 12 | 14.8 | 53.3 | 24.4 | 161.6 | TT   | 0    | E11-106R-005535 |
| 16.9 - 30                 | STANDARD | 94061976 | R1       | 132 A8 | 8  | W 15 L  | W 14 L      | 17   | 57.8 | 26.4 | 175.4 | TT   | 0    | E11-106R-005536 |
| 18.4 - 30                 | STANDARD | 94061983 | R1       | 135 A8 | 8  | W 16 L  | W 15 L      | 17.8 | 60.4 | 27.1 | 181.1 | TT   | 0    | E11-106R-005537 |
| 12.4 - 32                 | STANDARD | 94060849 | R1       | 121 A8 | 8  | W 11    | W 9 ; W 10  | 12.6 | 53.5 | 25   | 162.9 | TT   | 0    | E11-106R-005538 |
| 13.6 - 36                 | STANDARD | 94061747 | R1       | 125 A8 | 8  | W 12    | W 11        | 13.6 | 59.6 | 27.7 | 180.7 | TT   | 0    | E11-106R-005539 |
| 13.6 - 38<br>(14.00 - 38) | STANDARD | 94058693 | R1       | 127 A8 | 8  | W 12    | W 11        | 13.6 | 61.6 | 29   | 191.9 | TT   | 1    | E11-106R-005540 |
| 14.00 - 38<br>(13.6 - 38) | STANDARD | 94053582 | R1       | 127 A8 | 8  | W 12    | W 11        | 13.6 | 61.6 | 29   | 191.9 | TT   | 0    | E11-106R-004381 |
| 15.5 - 38                 | STANDARD | 94060344 | R1       | 129 A8 | 8  | W 14 L  |             | 15.5 | 62   | 28.8 | 189.5 | TT   | 0    | E11-106R-005541 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15.01.2025 21:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..