

FL 252 - Technische Daten



Description

FL 252 ist ein Reifen, der sich bestens für Heuernte-Anwendungen mit Rotorschwadern/Zettwendern sowie für Logistkarbeiten mit Gabelstaplern eignet. Dieser Reifen bietet ausgezeichnete Beständigkeit, während das spezielle Laufflächenmuster maximale Stabilität bei Hebearbeiten gewährleistet.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Rotorschwader
Industrie: Gabelstapler

Version	STANDARD
Type	TT
Tyre Size	5.00 - 8

Dimensions US Standard

Usa code	94006816
Ply Rating	8
Section Width (inch)	5.4
Overall Diameter (inch)	18.9
Rim Rec	3.00 D
Rim Alt	3.25 I

Load capacity (lbs)

	mph / psi	120
15 LOAD WHEEL		2725
15 STEER WHEEL		2095
5 OTHER VEHICLES		2725
15 OTHER VEHICLES		2095
STATIC SIDE LOADER		3165

Printed on 25.04.2024 18:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..