

FL 630 SUPER - Technische Daten



Description

FL 630 SUPER ist ein Flotationsreifen, der sich besonders für den Einsatz mit Anhängern, Tankwagen und Streumaschinen eignet. . Die robuste Struktur gewährleistet hervorragende Traktion, Beständigkeit und Grip auch in Kurven und während Manövern. Das spezielle Laufflächendesign steht für hohe Flotationsfähigkeit und reduziert die Bodenverdichtung neben ausgezeichneten Selbstreinigungseigenschaften. FL 630 SUPER erreicht Geschwindigkeiten von bis zu 70 km/h.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Streumaschine • Tankwagen • Anhänger

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 750/45 R 26.5 |
| LI/SS | 170 D |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 754 |
| Overall Diameter (mm) | 1349 |
| Static Loaded Radius (mm) | 606 |
| Rolling Circumference (mm) | 4147 |
| SRI (mm) | 650 |
| Rim Rec | AG 24.00 |
| ECE | E4-106R-001652 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 70 | 1750 | 1995 | 2240 | 2785 | 3170 | 3660 | 4150 | 4535 | 4970 | 5460 |
| 65 | 1920 | 2190 | 2460 | 3060 | 3480 | 4020 | 4560 | 4980 | 5460 | 6000 |
| 50 | 2325 | 2655 | 2980 | 3705 | 4215 | 4865 | 5520 | 6030 | 6610 | 7260 |
| 40 | 2615 | 2985 | 3350 | 4165 | 4735 | 5470 | 6205 | 6775 | 7430 | 8160 |
| 25 | 3035 | 3465 | 3890 | 4835 | 5500 | 6355 | 7205 | 7870 | 8630 | 9480 |
| 10 | 3460 | 3945 | 4430 | 5510 | 6265 | 7240 | 8210 | 8965 | 9830 | 10800 |

Printed on 19.04.2024 17:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..