

FL 639 - Technische Daten



Description

FL 639 ist ein feldorientierter radialer Flotationsreifen, der sich auch für Anwendungen mit Streumaschinen eignet. Die breite Aufstandsfläche bewirkt eine geringere Bodenverdichtung und somit einen erhöhten Ertrag der Kulturen. Die verstärkte Lauffläche und der Flankenschutz leisten ihren Beitrag zu einem verlängerten Produktlebenszyklus. FL 639 bietet erstklassige Traktion neben hervorragenden Selbstreinigungseigenschaften.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Streumaschine

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	168 B/156 B
LI/SS DRIVE WHEEL	156 B
LI/SS FREE ROLLING	168 B

Dimensions US Standard

Usa code	94063239
Section Width (inch)	24.1
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	141.4
Rim Rec	AG 20.00
ECE	E11-106R-006478

Load capacity (lbs)

mph / psi	12	15	17	20	23	26	29	32	35	38	41	44	46
30 FR	4800	5475	6150	6875	7600	8200	8800	9500	10200	10800	11400	11850	12300
30 DW	3420	3910	4400	4880	5360	5755	6150	6650	7150	7600	8050	8425	8800

Printed on 26.04.2024 05:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..