

FL 639 - Technische Daten



Description

FL 639 ist ein feldorientierter radialer Flotationsreifen, der sich auch für Anwendungen mit Streumaschinen eignet. Die breite Aufstandsfläche bewirkt eine geringere Bodenverdichtung und somit einen erhöhten Ertrag der Kulturen. Die verstärkte Lauffläche und der Flankenschutz leisten ihren Beitrag zu einem verlängerten Produktlebenszyklus. FL 639 bietet erstklassige Traktion neben hervorragenden Selbstreinigungseigenschaften.

UM

US Standard

Construction

RADIAL

Machinery

Landwirtschaft: Streumaschine

Version	STANDARD
Type	TL
Tyre Size	710/40 R22.5
LI/SS	161 D/172 A8

Dimensions US Standard

Usa code	94041176
Section Width (inch)	28.6
Overall Diameter (inch)	44.9
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	137.5
Rim Rec	AG 24.00
ECE	E4-106R-000801

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	2980	3440	3900	4740	5480	6320	7150	7700	8540	9280
40	3260	3780	4290	5200	6020	6930	7860	8470	9380	10200
30	3960	4570	5190	6300	7290	8400	9510	10250	11360	12350
25	4440	5140	5830	7080	8190	9440	10680	11520	12760	13870
15	5160	5970	6780	8220	9510	10970	12410	13380	14840	16110
5	5870	6800	7720	9370	10840	12490	14140	15230	16890	18350

Printed on 21.10.2020 09:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..