

## FL 639 - Technische Daten



### Description

FL 639 ist ein feldorientierter radialer Flotationsreifen, der sich auch für Anwendungen mit Streumaschinen eignet. Die breite Aufstandsfläche bewirkt eine geringere Bodenverdichtung und somit einen erhöhten Ertrag der Kulturen. Die verstärkte Lauffläche und der Flankenschutz leisten ihren Beitrag zu einem verlängerten Produktlebenszyklus. FL 639 bietet erstklassige Traktion neben hervorragenden Selbstreinigungseigenschaften.

### UM

US Standard

### Construction

RADIAL

### Machinery

Landwirtschaft: Streumaschine

Version	STANDARD
Type	TL
Tyre Size	710/40 R22.5
LI/SS	170 B/158 B

### Dimensions US Standard

Usa code	94063246
Section Width (inch)	28.6
Overall Diameter (inch)	44.9
Static Loaded Radius (inch)	19.8
Rolling Circumference (inch)	137.5
Rim Rec	AG 24.00
ECE	E11-106R-006479

### Load capacity (lbs)

mph / psi	12	15	17	20	23	26	29	32	35	38	41	44	46
30 FR	5080	5840	6600	7325	8050	8700	9350	10025	10700	11500	12300	12750	13200
30 DW	3640	4160	4680	5180	5680	6140	6600	7100	7600	8200	8800	9075	9350

*All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..*