

FL 639 - Datenblatt



Description

FL 639 ist ein feldorientierter radialer Flotationsreifen, der sich auch für Anwendungen mit Streumaschinen eignet. Die breite Aufstandsfläche bewirkt eine geringere Bodenverdichtung und somit einen erhöhten Ertrag der Kulturen. Die verstärkte Lauffläche und der Flankenschutz leisten ihren Beitrag zu einem verlängerten Produktlebenszyklus. FL 639 bietet erstklassige Traktion neben hervorragenden Selbstreinigungseigenschaften.

UM

US Standard

Construction

RADIAL

Machinery

Landwirtschaft: Streumaschine

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	Type	ECE	
560/45 R 22.5	STANDARD	94034260	152 D/163 A8	AG 16.00		21.4	42.4	19.1	130	TL	E4-106R-000627
600/50 R 22.5	STANDARD	94028153	159 D/170 A8	AG 20.00		24.1	46.1	20.5	141.4	TL	E4-106R-000802
600/50 R 22.5	STANDARD	94063239	168 B/156 B	AG 20.00		24.1	46.1	20.5	141.4	TL	E11-106R-006478
710/40 R 22.5	STANDARD	94041176	161 D/172 A8	AG 24.00		28.6	44.9	19.8	137.5	TL	E4-106R-000801
710/40 R 22.5	STANDARD	94063246	170 B/158 B	AG 24.00		28.6	44.9	19.8	137.5	TL	E11-106R-006479
850/40 R 26.5	STANDARD	94064779	173 D / 184 A8	AG 28.00		33.9	53.3	23.6	162.3	TL	E11-106R-006228

Printed on 21.10.2020 08:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..