

FLOTATION 351 - Technische Daten



Description

FLOTATION 351 ist ein diagonaler Flotationsreifen, der sich bestens zum Einsatz für Transportanwendungen mit Anhängern eignet. Die extra tiefen Stollen bieten hervorragende Traktionseigenschaften sowie eine längere Lebensdauer des Reifens. FLOTATION 351 ist der ideale Reifen auf nassen und feuchten Oberflächen, der hohe Tragfähigkeit bietet.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TL
Tyre Size	42 X 25.00 - 20
LI/SS	139 B

Dimensions International Standard

Ply Rating	16
Section Width (mm)	605
Overall Diameter (mm)	1110
Static Loaded Radius (mm)	508
Rolling Circumference (mm)	3302
Rim Rec	20.50 HF
Rim Alt	20.50 VF
ECE	E11-106R-004383
TRA Code	HF3

Load capacity (Kg)

km/h / bar	3.70
50	2430

Printed on 26.04.2024 16:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..