

## FLOTATION 351 - Technische Daten



### Description

FLOTATION 351 ist ein diagonaler Flotationsreifen, der sich bestens zum Einsatz für Transportanwendungen mit Anhängern eignet. Die extra tiefen Stollen bieten hervorragende Traktionseigenschaften sowie eine längere Lebensdauer des Reifens. FLOTATION 351 ist der ideale Reifen auf nassen und feuchten Oberflächen, der hohe Tragfähigkeit bietet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Anhänger

Version	STANDARD
Type	TL
Tyre Size	48 X 31.00 - 20
LI/SS	148 B

## Dimensions US Standard

Usa code	94026135
Ply Rating	12
Section Width (inch)	30.5
Overall Diameter (inch)	50.5
Static Loaded Radius (inch)	22
Rolling Circumference (inch)	153
Rim Rec	26.00 HF
Rim Alt	26.00 VF
ECE	E11-106R-004385
TRA Code	HF3

## Load capacity (lbs)

mph / psi	40
30	6950

Printed on 30.05.2023 03:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..