

## FLOTATION 647 - Technische Daten



### Description

FLOTATION 647 ist ein Reifen für landwirtschaftliche Geräte, der hervorragende Traktion auf weichem Boden und Grasflächen aufweist. Neben ausgezeichneten Selbstreinigungseigenschaften zeichnet sich das spezielle Laufflächenmuster durch eine breite Aufstandsfläche aus, die eine optimale Druckverteilung und beste Leistungen auf weichem Boden bietet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Version	STANDARD
Type	TL
Tyre Size	425/70 - 18
LI/SS DRIVE WHEEL	143 B
LI/SS FREE ROLLING	155 B

## Dimensions US Standard

Usa code	94064373
Section Width (inch)	17.1
Overall Diameter (inch)	41.9
Rim Rec	13.00
ECE	E11-106R-005851

## Load capacity (lbs)

mph / psi	51
30 FR	8550
30 DW	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26.03.2025 16:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..