

FLOTATION 647 - Datenblatt



Description

FLOTATION 647 ist ein Reifen für landwirtschaftliche Geräte, der hervorragende Traktion auf weichem Boden und Grasflächen aufweist. Neben ausgezeichneten Selbstreinigungseigenschaften zeichnet sich das spezielle Laufflächenmuster durch eine breite Aufstandsfläche aus, die eine optimale Druckverteilung und beste Leistungen auf weichem Boden bietet.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
260/75 - 15.3	STANDARD	94062768	119 A8	131 A8	9.00		10.8	30.9	14.3	93.7	TL	E11-106R-005838
520/50 - 17	STANDARD	94063314	147 B	159 B	AG 16.00		20.3	38	16.8	114.4	TL	E11-106R-005770
425/70 - 18	STANDARD	94064373	143 B	155 B	13.00		17.1	41.9	0	0	TL	E11-106R-005851

Printed on 27.04.2024 12:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..