

FLOTATION 648 T - Datenblatt



Description

FLOTATION 648 T ist besonders für den Transport auf Feld und Straße sowie für die Heuernte geeignet. Das spezielle Laufflächendesign ermöglicht den Transport besonders schwerer Lasten bei niedrigem Reifendruck und bietet dabei hervorragende Selbstreinigungseigenschaften. Der Reifen steht auch für erstklassige Traktion und Beständigkeit.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Mähdrescher

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/45 - 22.5	STANDARD	94029242	154 A8/150 B	166 A8/162 B	20	AG 16.00		21.7	42.1	18.7	126.1	TL	E4-106R-002046
550/45 - 22.5	STANDARD	94052066	147 A8/144 B	159 A8/156 B	16	AG 16.00		21.7	42.1	18.7	126.1	TL	

Printed on 23.04.2024 15:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..