

FLOTATION 648 - Technische Daten



Description

FLOTATION 648 ist im Einsatz auf dem Feld und auf der Straße mit Streuanwendungen erprobt. Einige Größen eignen sich für Erntemaschinen/Heupressen. Das spezielle Laufflächendesign ermöglicht den Transport besonders schwerer Lasten bei Niedrigdruck. Dies führt zu geringerer Bodenverdichtung und schützt gleichzeitig die Kulturen vor Schäden.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher • Streumaschine

Version	HD
Type	TL
Tyre Size	850/50 - 30.5
LI/SS DRIVE WHEEL	176 A8/173 B
LI/SS FREE ROLLING	189 A8/185 B

Dimensions US Standard

Usa code	94030286
Ply Rating	18
Section Width (inch)	33.5
Overall Diameter (inch)	65
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 28.00
ECE	E11-106R-004566

Load capacity (lbs)

mph / psi	33	34	36
5 FR	30280	31030	31790
10 FR	27250	27930	28610
20 FR	24220	24820	25430
25 FR	21630	22170	22710
30 FR	19470	19950	20390
5 DW	20870	21380	21910
10 DW	18780	19250	19720
20 DW	16690	17110	17530
25 DW	14900	15280	15650
30 DW	13410	13750	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.05.2025 18:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..