

## FLOTATION RIB 774 - Technische Daten



### Description

FLOTATION RIB 774 ist ideal für frei rollende Anwendungen bei der Heuernte und mit landwirtschaftlichen Geräten. Der Reifen wurde für besten Handlingkomfort entworfen und optimiert dabei die Einsatzzeiten bei hoher Tragfähigkeit und einem längerem Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Erntemaschine • Mähdrescher • Anhänger

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS FREE ROLLING	164 A8/160 B

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	600
<b>Overall Diameter (mm)</b>	1230
<b>Static Loaded Radius (mm)</b>	540
<b>Rolling Circumference (mm)</b>	3716
<b>Rim Rec</b>	AG 20.00
<b>ECE</b>	E11-106R-005943

## Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.10.2024 05:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..