

## FLOTATION TR 675 - Technische Daten



### Description

FLOTATION TR 675 ist sowohl für den Feld- als auch den Straßentransport geeignet. Er findet seinen Einsatz auf Anhängern und landwirtschaftlichen Geräten. Der FLOTATION TR 675 Reifen wurde so konzipiert, dass er hervorragende Traktion, neben hoher Tragfähigkeit und einem längerem Reifenleben bietet.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	550/45 - 22.5
LI/SS DRIVE WHEEL	154 A8/150 B
LI/SS FREE ROLLING	166 A8/162 B

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Section Width (mm)</b>	543
<b>Overall Diameter (mm)</b>	1070
<b>Rim Rec</b>	AG 16.00
<b>ECE</b>	E4-106R-002723

## Load capacity (Kg)

km/h / bar	3.00	3.50	4.00
10 FR	6270	6860	7420
20 FR	5645	6175	6680
30 FR	5020	5490	5935
40 FR	4480	4900	5300
50 FR	4030	4410	4750
10 DW	4440	4860	5250
20 DW	3995	4370	4725
30 DW	3550	3885	4200
40 DW	3170	3470	3750
50 DW	2855	3125	3350

Printed on 26.04.2024 09:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..