

## FLOTATION TR 678 - Technische Daten



### Description

FLOTATION TR 678 wurde speziell für Anhänger und landwirtschaftliche Geräte auf und abseits der Straße entwickelt. Dieser Reifen ermöglicht das Befördern schwerer Lasten bei geringem Reifendruck und gleichzeitig reduzierter Bodenverdichtung. Ferner zeichnet er sich durch erstklassige Traktion und optimale Selbstreinigungseigenschaften aus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger

Version	ARAMID + STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	173 A8

## Dimensions International Standard

Section Width (mm)	707
Overall Diameter (mm)	1165
Rim Rec	AG 24.00
ECE	E11-106R-006011

## Load capacity (Kg)

km/h / bar	6.00
40	6500

Printed on 18.04.2024 03:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..