

FORESTECH - Technische Daten



Description

FORESTECH ist ein BKT Reifen mit Stahlbändern, der sich für Anwendungen im Forstbetrieb mit Rückeschleppern eignet. Er verleiht ausgezeichnete Traktion auch bei schweren Betriebsbedingungen. Der robuste Wulst und der verstärkte Schulterbereich bieten hohe Durchstichfestigkeit und ein langes Reifenlebens. Somit können Sie sorgenfrei auch die schwierigsten Einsatzbedingungen im Forstbetrieb bewältigen.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Rückezug

Version	STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	161 A8/ 165 A2

Dimensions US Standard

Usa code	94059683
Ply Rating	20
Section Width (inch)	28
Overall Diameter (inch)	45.9
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	142.2
Rim Rec	AG 24.00
ECE	E11-106R-005273
TRA Code	LS2

Load capacity (lbs)

mph / psi	73
25	10200
20	11025
5	11400

Printed on 25.04.2024 09:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..