

FS 216 - Technische Daten



Description

FS 216 hat ein robustes, breites Stollenmuster mit optimiertem Winkel für verstärkte Traktionsleistung für Holzschlepper. Er verleiht ausgezeichnete Schnitt- und Reißfestigkeit auch unter kritischen Einsatzbedingungen und bietet jederzeit maximalen Schutz gegenüber möglichen Schäden.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Holzschlepper

Version	STEEL BELTED
Type	TL
Tyre Size	30.5L - 32

Dimensions US Standard

Usa code	94044313
Ply Rating	26
Section Width (inch)	30.5
Overall Diameter (inch)	72.7
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	215.2
Rim Rec	DH 27
Rim Alt	DH 27 B
TRA Code	LS2

Load capacity (lbs)

mph / psi	45	40
5	22000	-
20	-	15700

Printed on 25.04.2024 17:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..