

GF 304 - Technische Daten



Description

GF 304 eignet sich für Golfanwendungen mit Golfmobilen. GF 304 bietet besten Komfort und Bodenschutz. GF 304 ist auch in Ausführung "aramid-belted" mit Aramidbändern für verstärkte Durchstichfestigkeit erhältlich.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Golfmobil

Version	STANDARD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions International Standard

Ply Rating	4
Section Width (mm)	216
Overall Diameter (mm)	460
Static Loaded Radius (mm)	202
Rolling Circumference (mm)	1334
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003442

Load capacity (Kg)

km/h / bar	1.50
15	375

Printed on 22.04.2024 17:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..