

GF 304 - Datenblatt



Description

GF 304 eignet sich für Golfanwendungen mit Golfmobilen. GF 304 bietet besten Komfort und Bodenschutz. GF 304 ist auch in Ausführung "aramid-belted" mit Aramidbändern für verstärkte Durchstichfestigkeit erhältlich.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Golfmobil

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
18 X 8.50 - 8	ARAMID BELTED	4	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-005218
18 X 8.50 - 8	STANDARD	4	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-003442
18 X 8.50 - 8	STANDARD	6	7.00 I - 55 ; I - 70 ; I - 90		216	460	202	1334	TL	E11-106R-005197

Printed on 26.04.2024 09:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..