

GR 288 - Technische Daten



Description

GR 288 (G-2/L-2) ist ein vielseitiger Diagonalreifen für Planierer oder Lader. Er ist ideal zum Einsatz im Baugewerbe, zur Standortvorbereitung oder im Straßenbau auch auf weichem und schlammigem Gelände. Das selbstreinigende Laufflächenmuster verleiht ausgezeichnete Traktion. Ferner können Sie auf Grund der speziellen schnitt- und reißfesten Gummimischung ein langes Reifenleben erwarten.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Planierer • Radlader

OTR: Planierer

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions US Standard

Usa code	94014460
Ply Rating	20
Overall Width (inch)	23.4
Overall Diameter (inch)	63.4
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	188.3
Rim Rec	19.50/2.5
ECE	E11-106R-005181
TRA Code	G2/L2

Load capacity (lbs)

mph / psi	36	54
25	12000	-
5	-	24000

Printed on 23.04.2024 09:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..