

GRIP STAR - Technische Daten



Description

GRIP STAR ist ein agro-industrieller Reifen für Ladeanwendungen mit Teleskopladern, der ausgezeichnete Traktion und Selbstreinigungseigenschaften bietet. Es ist ein Ganzjahresreifen, der sich besonders für den Einsatz auf schlammigem Gelände eignet. GRIP STAR ist auch in Ausführung "special" erhältlich, die sich durch extra Schnitt- und Reißfestigkeit auszeichnet.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Teleskoplader

Version	SPECIAL
Type	TL
Tyre Size	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

Dimensions US Standard

Usa code	94035977
Ply Rating	16
Section Width (inch)	15.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	145
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

Load capacity (lbs)

mph / psi	58
20 FR LLV	10750
20 DW LLV	7610

Printed on 19.04.2024 19:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..