

IT 400 - Technische Daten



Description

IT 400 ist ein Reifen mit Rippenmuster zum vorwiegenden Einsatz auf der Straße für Tieflader in Transportanwendungen. Der Reifen eignet sich für Hochgeschwindigkeitsanwendungen und bietet deutliche Kraftstoffersparnis.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Tieflader

Version	STANDARD
Type	TT
Tyre Size	10.00 - 15
LI/SS	143/138 J

Dimensions International Standard

Ply Rating	18
Section Width (mm)	274
Overall Diameter (mm)	925
Static Loaded Radius (mm)	408
Rolling Circumference (mm)	2747
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0019537

Load capacity (Kg)

km/h / bar	9.70	8.90	8.10
15	4510	-	-
30	-	3640	-
100 LS	-	2725	-
100 LD	-	-	2360

Printed on 20.04.2024 17:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..